# **KOHLER**<sub>®</sub> **SDMO**



### HX 4000 C

PORTABLE POWER

Generating Sets Range INTENS

#### **PRODUCT ADVANTAGES**

- Entire group guaranteed 3 years
- HONDA Professional Engine •
- Solid and high-performance equipment

#### **Range INTENS**

Equipment that is robust, long-lasting and simple to use for repetitive operations in difficult conditions.



## HX 4000 C

#### **GENERAL SPECIFICATIONS**

Range	INTENS	
Frequency (Hz)	50 Hz	
Max power (kW) *	4	
Nominal voltage (V)	230	
Number of Phase	Single phase	
Fuel	Petrol	
Tank (L)	5.30	
75% cons. (l/h) *	2.10	
75% Autonomy (h) *	2.50	
Sound power level guaranteed LwA dB(A)	102	
Acoustic pressure level @1m in dB(A)	86	
Acoustic pressure level @7m in dB(A)	72	

#### **ENGINE SPECIFICATIONS**

Engine brand	HONDA
Engine type	GX270
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	270
Oil system capacity including filters (L)	1.10

#### ALTERNATOR SPECIFICATIONS

Technology	Brushless
0,	Drusiliess
AVR Regulation	No
Indication of protection	IP 23
Insulation class	Н

#### PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

#### DIMENSIONS AND WEIGHT

Length (cm)	71.50
Width (cm)	57
Height (cm)	49
Dry Weight (kg)	56

#### PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	49.50
Weight (kg)	58.50
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	162
weight of the packaged Pallet (kg)	361



HX 4000 C - PORTABLE POWER - Generating Sets INTENS

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



## HX 4000 C

**ACCESSORIES SUPPLIED** 



Funnel



User and maintenance manual

#### **OPTIONS**

	R01	This set includes the hour meter and the differential circuit breaker.
	R05M	The manual changeover switch is used to connect and disconnect a generating set manually to a domestic circuit when there is a power cut.
	RKB2	Trolley kit for the generating sets superior to 6kW
rear and a second	RH1	Cover for SDMO 's generating sets, welding sets and water pumps
	RPM	Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V
The second se	RPQ	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.



HX 4000 C - PORTABLE POWER - Generating Sets INTENS

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528. SDMO Industries - 270 rue de Kerervem - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com