



HP 2.26 H

PORTABLE POWER

Water Pumps Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- HONDA Professional Engine
- · Automatic priming
- Solid and high-performance equipment
- Offeres accessories
- High-pressure equipment

With nearly 6 bar of pressure, the HP 2.26 H can be used for high-pressure cleaning of machinery, such as agricultural vehicles. When combined with the nozzle kit, it can be used to suppress fires.

Range AQUALINE SPECIALIST

High performance under extreme conditions.













HP 2.26 H

WATER PUMP SPECIFICATIONS

| Range | AQUALINE SPECIALIST |
|--|---------------------|
| Type liquid | High voltage use |
| Suction diameter [mm] | 50 |
| Backflow diameter (mm) | 50 |
| Outflow maximum (L/min) | 440 |
| Outlflow maximum (m3/h) | 26.40 |
| Lifting height (m) | 57 |
| Suction height (m) | 8 |
| Granulometry (mm) | 8 |
| Automatic priming | Yes |
| Fuel | Petrol |
| Tank (L) | 3.10 |
| 75% cons. (I/h) * | 0.90 |
| 75% Autonomy (h) * | 3.40 |
| Sound power level guaranteed LwA dB(A) | 108 |
| Acoustic pressure level @1m in dB(A) | 92 |
| Acoustic pressure level @7m in dB(A) | 77 |

ENGINE SPECIFICATIONS

| Engine brand | HONDA |
|---|---------|
| Engine ref. | GX160 |
| Distribution | O.H.V. |
| Start | Starter |
| Oil shutdown | Oui |
| Displacement (cm3) | 163 |
| Oil system capacity including filters (L) | 0.60 |

DIMENSIONS AND WEIGHT

| Length (cm) | 41.50 |
|-----------------|-------|
| Width (cm) | 54.50 |
| Height (cm) | 45.50 |
| Dry Weight (kg) | 30 |

PACKAGING

| Packaging type | Box |
|------------------------------------|--------|
| Length (cm) | 54 |
| Width (cm) | 42 |
| Height (cm) | 45 |
| Weight (kg) | 35 |
| Pallet type | 120/80 |
| Number of box by pallet | 12 |
| Pallet height (cm) | 148 |
| weight of the packaged Pallet (kg) | 430 |





ACCESSORIES SUPPLIED



Inlet filter

RHO

Circlips

Screw-on connectors

User and maintenance manual

OPTIONS



RBH1 Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5 Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



Cover for SDMO 's generating sets, welding sets and water pumps