



TR 3.60 H

PORTABLE POWER

Water Pumps Range AQUALINE INTENS

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Resistant pump-barrel
- Automatic priming
- Easy acces to the turbine
- Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

Range AQUALINE INTENS

Designed for water with low solid content.

















TR 3.60 H

WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	900
Outlflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3.10
75% cons. (I/h) *	0.90
75% Autonomy (h) *	3.40
Sound power level guaranteed LwA dB(A)	105
Acoustic pressure level @1m in dB(A)	91
Acoustic pressure level @7m in dB(A)	76

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (L)	0.60

DIMENSIONS AND WEIGHT

Length (cm)	50.50
Width (cm)	39.80
Height (cm)	46.60
Dry Weight (kg)	29

PACKAGING

Packaging type	Box
Length (cm)	51.50
Width (cm)	42
Height (cm)	48
Weight (kg)	34.50
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	157
weight of the packaged Pallet (kg)	424





TR 3.60 H

ACCESSORIES SUPPLIED



Inlet filter

RHO

R12

Circlips



Screw-on connectors

User and maintenance manual



OPTIONS

RBH1 Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5 Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



Cover for SDMO 's generating sets, welding sets and water pumps



Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.

